



## CONSTRUCTION HOTES

- A. 3" STEEL PIPE, TYPICAL AT MAIN FRAME SUPPORTS.
- B. 1-1/2"\* STEEL PIPE TRUSS SUPPORT WELDED TO 1/4" STEEL PLATES, TYPICAL.
- C. PREFAB COMPOSITE METAL ROOF SEE DETAILS A/.7, B/.7 ON SHEET 2533.7.
- D. 1/8" X 2-1/2" X 1-1/4" STEEL "T"
  CONTINUOUS ROOF SUPPORT STRIP.
  SEE DETAILS A/.13, B/.13 ON SHEET
  2533.13.
- E. 1/4" X 1-1/2" X 2" STEEL PLATE WELDED TO STEEL PIPE.
- F. 1/4" STEEL PLATE WELDED TO STEEL PIPE.
- G. CAP ENDS OF PIPE WITH 1/8" STEEL PLATE, WELDED ALL AROUND.
- H. 3/8" Ø STEEL BOLT WITH SPOT WELDED NUT.
- 16 GA CONTINUOUS STEEL DRIP SEE DETAIL B/.12 ON SHEET 2533.12.
- J. RADIUS POINT FOR 3"\* MAIN FRAME PIPE (SEE SHEET 2533.6).
- K. CENTER PIPE WITH VERTICAL CENTERLINE OF SUPPORT BELOW.

CITY OF ALBUQUERQUE

REVISIONS

BUS SHELTER 'A' STEEL PLATE CONNECTION

DWG.2533.11

JUNE 1991